

Caterham CSR Superlight Set-Up Specifications

	Front Starting Spec	Front Final	Rear Starting Spec	Rear Final
Weight @ Kerb	145/150kg		154/150kg	
Weight @ mid-laden (+75kg)	154/159		183/179kg	
Spring Rate	150 lb/in		180 lb / in (helper type)	
Ride Height	140-145mm	140mm	158-163mm	165mm
Camber	0.25-0.5 deg negative	LHS: 0.4 deg RHS: 0.3 deg	1.75-2.0 deg negative	LHS: 1.7 deg -ve RHS: 2.0 deg -ve
Caster	5.5-6.0 deg	LHS: 6.5 deg RHS: 5.5 deg	N/A	
Bump Steer	1.0-1.5mm toe out @ 50mm bump		1.0-1.5mm toe in @ 50mm bump	
Toe (static)	0 deg +/-5'	0 deg	1.5mm toe in per side	2mm toe in per side
Push Rod Length	290mm		N/A	
Damper Setting	F36		R89	
Rack Spacers	Varies		N/A	
Rear Tie Rod Spacers	N/A		Varies	
Measurement to bump stop contact	14mm		26mm	
Spring Length (damper assembly off car)	188mm (nominal)		262mm	
Camber Spacers	Adjustment = +/- 0.3 deg / turn		7.0mm nominal rate = +/- 0.25 deg / mm	
Tires & Wheels	6.5 x 15 ET13 machined to ET40 195 45 R15		9 x 15 ET8 245 40 R15	
Tire pressures	24 psi cold		23 psi cold	